

CHAPTER 1

INTRODUCTION

February 22, 2000

Revised X, 2018

v. 10/12/17, 171012 chapter 1 .docx

Table of Contents

1.1	Purpose	1 - 2
1.2	Contents.....	1 - 2
1.3	Objectives.....	1 - 2
1.4	Planning Concepts.....	1 - 3
1.4.1	Drainage is a regional phenomenon	1 - 3
1.4.2	Storm drainage is a sub-system of the total urban system.....	1 - 3
1.4.3	Urban areas have two drainage systems.....	1 - 3
1.4.4	Runoff routing.....	1 - 3
1.4.5	Stormwater runoff as a resource.....	1 - 4
1.4.6	Utilize the features and functions of the natural drainage system.....	1 - 4
1.4.7	Post-development flow rates shall not exceed pre-development conditions	1 - 4
1.4.8	Design the stormwater management system from the point of outflow	1 - 4
1.4.9	Provide regular maintenance.....	1 - 4
1.4.10	Preventative and corrective actions	1 - 4
1.4.11	Stormwater quality	1 - 5
1.5	Criteria summary	1 - 5
1.5.1	Drainage design and technical criteria	1 - 5
1.5.2	Minor and major drainage systems	1 - 5
1.5.2.1	Minor drainage systems.....	1 - 5
1.5.2.2	Major drainage systems	1 - 5
1.5.3	Storm runoff computation	1 - 6
1.5.4	Detention.....	1 - 6
1.5.5	Streets.....	1 - 6
1.5.6	Flood corridor management	1 - 7
1.5.7	Floodplain management	1 - 7
1.5.8	NPDES construction site activities	1 - 7
1.5.9	Water quality.....	1 - 8
1.6	Interrelationship between stormwater quantity and quality management.....	1 - 8
1.7	Limitations.....	1 - 8
1.8	Updating	1 - 9

APPENDICES

Appendix 1 Glossary of Key Terms

1.1 Purpose

Providing adequate drainage in urban areas is a necessary component in maintaining the overall health, welfare, and economic well-being of a community. Drainage is a regional feature that affects multiple jurisdictions and all parcels of land. It is important to develop drainage policy that balances both public and private considerations as well as economic, environmental and safety issues.

Certain underlying principles should be applied when planning drainage facilities. These principles apply to both water quantity and water quality management. Policy statements and technical criteria serve as the implementation tools for the underlying drainage principles.

The purpose of this Drainage Criteria Manual, in conjunction with the development of overall master planning of watersheds throughout the Lincoln, Nebraska area, is to provide drainage facilities in urban areas that avoid the disruption of the community while improving the overall health and welfare of the region in an economic way.

This Drainage Criteria manual shall apply within the corporate limits of the City and within the three-mile jurisdictional boundary of the City.

1.2 Contents

This Drainage Criteria Manual has been prepared by the City of Lincoln, Nebraska and the Lower Platte South Natural Resources District (LPSNRD) to provide guidance to design engineers, hydrologists, water quality specialists, and others involved in the management of stormwater runoff. An extensive collaborative effort was undertaken in the original Manual preparation that involved input from a project Management Committee, Advisory Committee, and the general public. The committees were formed to represent a broad and diverse group of interests throughout the City, including: builders, developers, environmental groups, public works, neighborhood associations, etc. Meetings and workshops were regularly held to discuss and reach consensus on important drainage, flood control, and water quality protection issues specific to the City of Lincoln.

The Manual is comprised of ten technical chapters that provide guidance on the major aspects of urban stormwater management and drainage facility design. The Manual is intended to be an effective and practical resource that provides users with proven engineering approaches along with illustrative examples. The Manual represents a compilation of a large amount of technical information in a single document, which should help minimize the need for multiple outside references.

The manual was updated in 2018 to update it, provide in a more readable digital format and overall make it a more useable document.

It is assumed that the user has basic knowledge of hydraulics, hydrology, and stormwater management concepts. While some theory is presented in the Manual, the text is devoted more to the practical application of the theory, as it relates to drainage management and design.

1.3 Objectives

Drainage, flood control, and water quality protection in the City of Lincoln and its surrounding areas are an integral part of the comprehensive planning process. Drainage represents only one component of a larger urban system. The objectives of the City of Lincoln with respect to drainage, flood control, and water quality protection are to:

- Protect the general health, safety, and welfare of the residents of the City of Lincoln
- Minimize property damage from flooding; including minimization of localized neighborhood flooding
- Ensure that new buildings and facilities are free of flood hazard from major and minor storm events
- Minimize water quality degradation by limiting the amount of sediment generation and erosion of channels
- Retain open spaces, specifically along natural drainage ways

- Plan for large and small flooding events by providing both major and minor drainage systems
- Implement reasonable, cost effective best management practices (BMPs) for sediment control and water quality enhancement
- Manage stream and drainage channel corridors to promote environmental diversity and to protect buildings and facilities from damage by channel erosion
- Stabilize channels to, among other things, minimize the disruption of existing infrastructure such as bridges and utility lines
- Comply with the City of Lincoln National Pollutant Discharge and Elimination System (NPDES) permit requirements
- Develop equitable methods to adequately fund construction, operation and maintenance, and administration of an up-to-date stormwater management program
- Minimize future operating and maintenance expenses
- Educate the public on stormwater policies and administrative procedures
- Build a stormwater program based on understanding and cooperation with builders and developers, providing for effective administrative authority for the City and LPSNRD

The application of this Manual in the overall planning of new development is practical and economical; however, there are many built-up areas within and around the City of Lincoln which will not conform to the drainage standards proposed in this Manual. In fact, the problems associated with these areas provided some of the impetus for the development of the original Manual. The up-grading of built-up areas to conform to the policy, criteria, and standards contained in this Manual may be difficult, and sometimes impractical. Therefore, in the planning of drainage improvements in built-up areas, it is recommended that the design approaches presented in this Manual be adjusted for practicality.

1.4 Planning Concepts

The following general principles apply when planning for and designing urban storm drainage systems:

1.4.1 Drainage is a regional phenomenon

Drainage is a regional phenomenon that does not respect the boundaries between government jurisdictions or between public and private properties. Therefore, a successful plan must integrate regional jurisdictional cooperation, where applicable, to accomplish established goals. The City of Lincoln will seek the cooperation of LPSNRD and Lancaster County to minimize the contribution of all storm drainage systems to flooding and in the preparation and implementation of master drainage plans.

1.4.2 Storm drainage is a sub-system of the total urban system

Drainage is a sub-system of all urbanization. The planning of drainage facilities must be included in the urbanization process. The first step is to include drainage planning with all regional and local urban master plans.

1.4.3 Urban areas have two drainage systems

Urban areas are comprised of two drainage systems. The first is the minor or primary system, which is designed to provide public convenience and to accommodate relatively moderate frequent flows. The other is the major system, which carries more water and operates when the rate or volume of runoff exceeds the capacity of the minor system.

1.4.4 Runoff routing

Analysis and design of drainage systems should not be based on the premise that problems can be transferred from one location to another.

1.4.5 Stormwater runoff as a resource

Stormwater runoff and the facilities to accommodate the runoff can be an urban resource when properly included in the urban system. Drainageways can provide environments for various life forms such as aquatic life, mammals, birds, and vegetation. In many cases the drainage facilities can provide areas for active and passive recreation for citizens to enjoy. Although sometimes a liability to urbanization, stormwater runoff can be beneficial as an urban resource.

When stormwater runoff is treated as a resource, water quality aspects become important. As such, it is important to implement best management practices (both structural and nonstructural) and effective erosion and sediment control measures.

Due to the multi-purpose potential of stormwater runoff, natural drainage channels should be given priority consideration in the preparation of drainage system designs and should be included as an integral part of the landscape.

1.4.6 Utilize the features and functions of the natural drainage system

Every site contains natural features that may contribute to the management of stormwater under existing conditions. Each development plan should carefully map and identify the natural system. Natural engineering techniques can preserve and enhance the natural features and processes of a site and maximize post-development economic and environmental benefits. Good designs improve the effectiveness of natural systems, rather than negate, replace, or ignore them.

1.4.7 Post-development flow rates shall not exceed pre-development conditions

In new developments or in redevelopments requiring subdivision code changes, post-development peak flow rates shall not exceed pre-development peak flow rates for the 2-year, 10-year and 100-year discharges at the project property line and in accordance with other chapters of this Drainage Criteria Manual, unless waived by the Director of Public Works and Utilities.

1.4.8 Design the stormwater management system from the point of outflow

The downstream conveyance system should be evaluated to ensure that it has sufficient capacity to accept design discharges without adverse backwater impacts on the proposed conveyance system, or downstream impacts such as flooding, streambank erosion, and sediment deposition. Starting tailwater conditions for the major and minor design storm flow should be determined.

1.4.9 Provide regular maintenance

Failure to provide proper maintenance reduces both the hydraulic capacity and pollutant removal efficiency of the system. Effective maintenance relies on clear assignment of tasks and a regular inspection schedule.

1.4.10 Preventative and corrective actions

In existing urban settings, it may be necessary to develop a stormwater management strategy based upon both preventive and corrective measures. For example, structural corrective measures such as inlets, storm drains, interceptor lines, channelized stream sections and reservoirs affect and control storm runoff and floodwaters directly. Nonstructural corrective measures, such as floodproofing and land use adjustments, help limit activities in the path of neighborhood storm runoff or in river floodplains. Preventive actions available for reducing storm runoff and flood losses include: flood-prone land acquisition, floodplain regulations, and control of land uses within flood-prone areas.

1.4.11 Stormwater quality

Post construction stormwater management plans shall be submitted for review for both development and redevelopment projects per Chapter 8 of the Drainage Criteria Manual.

1.5 Criteria summary

1.5.1 Drainage design and technical criteria

The design criteria presented in this Manual are based on national engineering state-of-the-practice for stormwater management, modified to suit the needs of Lincoln specifically. Extensive input from the City of Lincoln, LPSNRD, and the public was used to develop and refine the criteria. The criteria are intended to establish guidelines, standards, and methods for effective planning and design. The criteria should be revised and updated as necessary to reflect advances in the field of urban drainage engineering and urban water resources management.

1.5.2 Minor and major drainage systems

Every urban area has two separate and distinct drainage systems, whether or not they are actually planned for and designed. One is the minor system and the other is the major system. To provide for orderly urban growth, reduce costs to taxpayers, and obviate loss of life and property damage, both systems must be planned and properly engineered.

1.5.2.1 Minor drainage systems

The minor drainage system is typically thought of as storm drains and related structures, such as inlets, curbs and gutters. The minor system is normally designed for floods with return frequencies of 2-years to 10-years, depending upon the kind of land use.

For Lincoln, the minor drainage system design will be based on the 5-year to 10-year return frequency storms, depending on the design application. For residential areas, the 5-year storm is appropriate, while for downtown areas and industrial/commercial areas, the 10-year storm is appropriate.

During design, the hydraulic grade line for all enclosed systems shall be determined to ensure that inlets act as inlets, not outlets. All easements for storm drain pipe should be a minimum of 30 feet wide. In situations where the engineer can clearly demonstrate that an easement less than 30 feet is adequate, the City may consider such a request. Easements for storm drain pipe and surface water flowage shall be used where a drainageway must be maintained to carry stormwater flow in excess of the storm drain pipe capacity. The easement cross-section shall accommodate the depth and width of flow from the 100-year storm. The width must also be designed to allow for access of maintenance equipment during the major storm.

Design storms equal to the 2-year, 10-year and 100-year frequency events shall be used in the design of detention/retention facilities for water quantity. If a detention/retention facility is used for both water quantity and water quality it shall also take into account the water quality storm event.

1.5.2.2 Major drainage systems

The major drainage system is designed to convey runoff from, and to regulate encroachments for, large, infrequently occurring events. When development planning and design do not properly account for the major storm flow path, floodwaters will seek the path of least resistance, often through individual properties, thus causing damage. An assured route of passage for major storm floodwaters should always be provided such that public and private improvements are not damaged. For subdivisions in Lincoln, this need is to be provided for both in watershed headwaters settings and along major drainageways.

The 100-year return frequency storm shall be the major drainage system design storm for all new developments. Runoff from the 100-year storm event shall pass through a development without flooding buildings, homes, or residential lots. Overland flow routes can be provided using streets, swales, and open space.

Open channels for transportation of major storm runoff are desirable in urban areas and use of such channels is encouraged. Open channel planning and design objectives are best met by using natural, or natural-type channels, which characteristically have slow velocities, and a large width to depth ratio. Optimum benefits from open channels can best be obtained by incorporating parks and greenbelts with the channel layout.

To the extent practicable, open channels shall follow the natural channels and shall not be filled or straightened significantly. Effort must be made to reduce flood peaks and control erosion so that the natural channel features are maintained. Channel improvement or stabilization projects are encouraged which minimize use of visible concrete, riprap, or other hard stabilization materials to maintain the riparian characteristics.

1.5.3 Storm runoff computation

The calculation of the storm runoff peaks and volumes is important to the proper planning and design of drainage facilities. Peak runoff values shall be calculated by using either the rational method, the NRCS method as outlined TR-55, the SCS method in the U.S. Army Corps of Engineers (USACE) HEC-HMS software or other rational or SCS methodological software as appropriate.

1.5.4 Detention

Detention facilities shall have release rates which do not exceed the pre-development peak discharge rates for the 2-year, 10-year and 100-year storms. Hydrologic conditions as of 1 August 1999 shall be used to determine peak release rates for pre-development conditions. Submittal of hydraulic design calculations is required to document that major and minor design storm peak flows are attenuated. On-site and regional facilities shall be designed with adequate access and sediment storage right-of-way (including sediment fore-bays) to facilitate maintenance.

On-site detention is required unless the master planning process or a regional analysis has shown that the detention requirement can be transferred to a regional detention cell. On-site detention, however, may still be necessary to provide for receiving stream channel stability maintenance. Extended detention design may be utilized to enhance stormwater quality benefits, including increased sediment removal.

Where feasible, strategically located regional detention cells may be used to reduce flow peaks from major storm events. Funding mechanisms may be developed to allow joint investment by benefitted parties in regional facilities, where transfer of detention requirements proves to be feasible and beneficial.

On-site and regional detention facilities shall be designed with adequate access and sediment storage right-of-way (including sediment forebays) to facilitate maintenance. Unless private maintenance of on-site detention facilities is acceptably performed, necessary maintenance by government forces shall be provided. The cost of this government service shall be allocated to responsible parties.

The owner shall provide record drawings of the storage facility to the Public Works & Utilities Department.

1.5.5 Streets

The primary drainage functions of streets are to convey minor stormflows quickly and efficiently to the storm drain or open channel drainage with minimal interference to traffic movement and to provide an emergency passageway for the major storm flows without causing damage to adjoining properties, while allowing for safe movement of emergency vehicles.

The allowable use of streets for new land development in Lincoln for minor and major storms runoff in terms of pavement encroachment is presented in Chapter 3.

1.5.6 Flood corridor management

In all watersheds within the Existing Urban Area where a FEMA mapped floodplain has not been delineated, development shall preserve a corridor in channels which drain greater than X {parking lot item} acres. In all watersheds within New Growth Areas, development shall preserve a corridor in all channels which drain greater than X acres or have a defined bed and bank.

{To be revised} The width of minimum flood corridors shall be equal to the channel bottom width, plus 60 feet, plus six times the channel depth, and the corridor shall be centered on the channel or aligned such that the corridor follows the natural flow of flood waters.

The corridor will be centered on the channel or aligned such that the corridor follows the natural flow of floodwaters. Riparian vegetation and the existing grade within the identified flood corridors shall be preserved or enhanced to the maximum extent practicable, or mitigated during the development planning and construction processes when impacted by allowable encroachments. Individual areas of encroachments of the riparian vegetation and encroachments of fill into the existing grade will be permitted for operation, maintenance and repair, channel improvements, stormwater storage facilities, and utility crossings. Individual areas of encroachment may also be permitted for parks, pedestrian/bike trails, recreational uses, and public purposes, provided the encroachments are minimal and the uses are generally consistent with the purpose of the corridor.

Sequencing and mitigation for encroachments into Minimum Flood Corridors is required as described in Chapter 2.05 of the Design Standards and Chapter 10 of this manual.

Flood corridors delineated during development of land shall be legally described and recorded.

1.5.7 Floodplain management

Flood criteria for Existing Urban Areas and New Growth Areas are provided in Chapter 10 of the Drainage Criteria Manual. For a defined area of Salt Creek known as the Salt Creek Flood Storage Area from Superior Street to Calvert along Salt Creek there are specified allowable fill areas for each of the flood storage areas per ordinances in the zoning codes (Chapter 27) and as specified on the city's GIS system.

1.5.8 NPDES construction site activities

A NPDES "notice of intent" and a Stormwater Pollution Prevention Plan (SWPPP) shall be required before land disturbance or vegetation removal activities occur on any site greater than or equal to 1.0 acre in size. The submittal of the application will be an electronic submittal to the State of Nebraska Department of Environmental Quality for the state permit. This application will be electronically submitted to the City from the State, wherein the City will review it for City approval. Approval of the permit application will be provided when both the City and State approve the permit application. Structural and non-structural best management practices (BMPs) are required to address erosion and sediment control concerns. The SWPPP shall be prepared by a designated erosion control designer. A designated erosion control designer shall be: a licensed professional engineer, landscape architect; a professional in Erosion and Sediment Control, certified by the Soil and Water Conservation Society; or a person with similar erosion and sediment control training and knowledge certified by a nationally recognized erosion and sediment control association. As one condition of approval, a construction schedule shall be included which indicates installation of as many of the proposed BMPs as are feasible before any land disturbing activity is conducted, including site grubbing. The schedule will also indicate a plan to limit the duration of exposure of disturbed land.

Contractors and developers shall contact the City on the business day prior to performing land disturbance or vegetation removal on any site greater than or equal to 1.0 acre. Construction sites will be inspected periodically for compliance with submitted SWPPPs.

1.5.9 Water quality

Both structural and nonstructural best management practices (BMPs) are required that address long-term stormwater quality enhancement. Effective, reasonable, and cost-effective BMPs should be selected for implementation on a site-specific basis and in a manner that is consistent with existing basin master plans. For water quality control purposes, guidelines and requirements are shown in Chapter 8.

The following is a list of structural BMPs that can be considered:

- Create temporary ponding areas on parking lots and in landscaped or turfed open areas of building sites
- Use porous pavement for remote parking areas
- Reduce the amount of impervious area directly connected to the storm drain system
- Intentionally create longer vegetated drainage paths for minor storm events
- Encourage use of constructed wetlands
- Develop multipurpose extended detention facilities
- Use retention facilities (wet ponds) where feasible

The following is a list of non-structural BMPs that can be considered:

- Use of appropriate vegetation to reduce the need for fertilizer and pesticides
- Preservation of environmentally sensitive areas to protect them from development or other disruption
- Set aside more open space
- Preserve or re-establish riparian vegetation
- Implement staged grading of developments to minimize the amount of land disturbed at one time

Additional structural and nonstructural BMPs are presented in Chapter 8 of the Manual.

1.6 Interrelationship between stormwater quantity and quality management

With urbanization, the hydrology of a watershed changes in three important ways: (1) the total runoff volume is greater, (2) the runoff occurs more rapidly, and (3) the peak discharge is greater. The increase in runoff volume results from the decrease in infiltration and depression storage. The shortened time base results from the greater flow velocities in the drainage system. The increase in peak discharge is the inevitable consequence of a larger runoff volume occurring over a shorter time. This increase in peak discharge for any storm means a related high discharge occurs more frequently.

More frequent occurrences of high discharges may cause or intensify channel erosion problems, disrupting the riparian habitat both where the erosion occurs and where the additional sediment is deposited downstream.

The City of Lincoln has seen the consequences of rapid urbanization on the water quality of its receiving streams. Consequently, this Manual is part of an effort to more effectively manage both stormwater quantity and quality. By implementing well planned and designed engineering approaches, the necessary measures can be taken to minimize the cumulative water quality and water quantity impacts that result from urbanization.

1.7 Limitations

The interpretation and application of the provisions in this Manual shall be the minimum requirements for promotion of the health, safety, convenience, order and general welfare of the community. The standards, however, should not be construed as rigid criteria. Rather, the criteria are intended to establish guidelines, standards and methods for sound planning and design. The City may set aside these criteria in the interest of the health, safety, convenience, order and general welfare of the community.

The Manual is not intended to interfere with, abrogate, or annul any other regulation, statute, or other provision of the law. Where any provision of this Manual imposes restrictions different from those imposed by any other

provision of this Manual or any other regulation or provision of law, that provision which is more restrictive or imposes higher standards shall govern.

1.8 Updating

The policies and criteria presented in this Manual may be amended as new technology is developed and/or experience is gained in the use of the criteria indicate a need for revision. Amendments and revisions to the Manual will be made by the City of Lincoln when necessary to accomplish the goal of reasonable public protection from surface water runoff.